# RECREATIONAL VEHICLE WIRING NONPERMANENT-TYPE

## (TRAILERS, CAMPERS, TRUCK CAMPERS, MOTOR HOMES AND BOATS)

#### 1. GENERAL

1.001 This addendum supplements Section 461-220-101, Issue 1. Place this pink sheet ahead of page 1 of the section.

- 1.002 This addendum is issued for the following reasons:
  - (a) To add information on the C weatherproof cord, and
  - (b) To clarify the location of the station protector at marina installations.

### 2. CHANGES TO SECTION

- 2.001 On page 1, under ORDERING GUIDE, add:
  - Cord, Weatherproof, C (used with RV and boats, Fig. 5.1).
- 2.002 On page 3, following paragraph 2.05, add the following paragraph:
- 2.05.1 The C weatherproof cord is the same as
  the B weatherproof cord except that the
  female plug on the recreational vehicle or boat
  end is replaced with space-tipped leads for terminating

the cord directly in a 500- or 2500-type telephone set. An "S" hook assembly is provided for fastening the cord by means of the ringer mounting screw. Terminate the leads as follows: (BK) for tip, (W) for ring, and (G) for ground.

- 2.003 On page 10, revise paragraph 3.11 to read as follows:
- Jacks on docks should be mounted on posts 3.11 or in wells provided by the marina owner. To prevent damage, do not mount the jack on the water or walkway side. Usually the post or pedestal will be the same one on which power is mounted. No station protector or bonding is to be placed on the boat. Mount the protector at the last permanent terminal or housing (which will usually be ashore) so that an adequate ground may be obtained. Refer to the sections on station protection and grounding in Division 460. Where individual protectors are required, use the 123- or 128-type with the 305A mounting (or equivalent). Provide a ringer simulator or equivalent at the dock jack if required.
- 2.004 On the bottom of page 1, delete the copyright notice and add the following: Not for use or disclosure outside the Bell System except under written agreement.

#### NOTICE

Not for use or disclosure outside the Bell System except under written agreement




Fig. 5.1—Securing C Weatherproof Cord in Telephone
Set