14A COMMUNICATION SYSTEM (COM KEY* 1434)

1. GENERAL

1.001 This addendum supplements Section 518-450-102, Issue 3. Place this pink sheet ahead of Page 1 of the section.

1.002 This addendum is reissued to:

- Provide additional information related to the Federal Communications Commission's (FCC) Registration Program
- Revise information supplied in Issue 1 of the addendum.

1.003 This addendum was issued to add information on the treatment of central office (CO) lines under the FCC Registration Program and to add the output capacity of the 457C KTU (Paging Amplifier Circuit).

2. CHANGES TO SECTION

Issue 1 Changes

- 2.001 On Page 3, after paragraph 1.05, add the following paragraph:
- 1.06 Incoming CO lines to be installed in compliance with the FCC Registration Program must

be routed through a standard network interface. Information on approved interfaces is contained in Sections 463-400-100 through 463-400-150.

2.002 On Page 21, at the end of paragraph 2.35, add the following: The output of the 457C KTU is 3 watts of peak power.

Issue 2 Changes

2.003 Revise paragraph 1.06 as follows:

The 14A Communication System has not 1.06 been registered with the FCC and new systems will not be manufactured after January 1, 1980. Also after January 1, 1980, connection of customer-provided equipment (CPE) or telephone company-provided equipment to the 14A Communication System requires the use of a 33B voice coupler when providing music-on-hold and the 415C, 454C, 471C, and 479C key telephone units (KTUs) must be used when providing related services. Previously connected or Class C system components may be used for additions and maintenance at grandfathered installations for the life of the equipment, provided they are not modified. Class C components may also be used in new installations after January 1. 1980.

*Trademark of AT&T.

NOTICE

Not for use or disclosure outside the Bell System except under written agreement

Printed in U.S.A.

Page 1 1 Page